


SUPERVAC

BATTERY PPV COMPARISON TABLE



Battery	SuperVac V18-BD	Ramfan EX50Li	Blowhard BH-20	Leader Batfan 45	Tempest VS-1
Swappable Batteries	YES	YES	NO	NO	YES
Battery Availability	Commercial Available	On Request	On Request	On Request	On Request
Battery	DeWalt FlexVolt 20-60V	Proprietary 40V Li-Ion	Proprietary Li-Ion	Proprietary NiMH	Proprietary 48V Li-Ion
Charge Time	1.5 Hours	6 Hours	2.5 Hours	2.5 Hours	4 Hours
Runtime (min)	45	40	35 Avg.	45	70
Battery Warranty	3 Years	.5 Year	1 Year BH-20	1 Year	2 Years
Performance					
AMCA Certified	AMCA 240	AMCA 240	Not AMCA Certified	Not AMCA Certified	AMCA Certified
Published Airflow (cfm)	10,840	8,939	10,200	17,700	10,887
Physical Specs					
IP Rating	IP65	IP66	IP66	IP66	IP65
Weight with Bat. (lbs)	46	54	59	58	52
Blade Diameter	18"	18"	20"	16.5"	18"
Dimensions HxWxD	25.75" x 25.75" x 11.75"	22" x 21" x 12"	24" x 24" x 10"	21" x 21.25" x 11"	26" x 23" x 11"
Other					
Fan Warranty	5 Year	3 Year	1 Year	2 Year	5 Year
Able to Plug into AC	Optional	YES	YES	YES	YES
Forward-Facing LEDs	Standard	Standard	No	Standard	Standard
Handling					
Tilt	-90 to +90	0 to +35	0 to +90	-65 to +90	-12 to +25
Transport Method	6" Rubber Wheels	Shoulder Strap (sold sep)	Shoulder Strap	Shoulder Strap	4" Wheels
Follows ISO 11228	YES	NO	NO	NO	YES
Additional Cost Accessories	Duct, Mister, Foam, Door Bar, Truck Mount, Shoulder Strap	Shoulder Strap, Wheel Kit, Duct, Mister, Door Bar, Truck Mount	Duct, Mister	Duct, Mister, Foam	None

For a demo or pricing information, please contact:

800-525-5224

| info@supervac.com

| www.supervac.com