

V16-BW-SP-WH Variable-Speed Battery Fan

Compact. Lightweight. And reliable. Introducing the all-new Super Vac 16" variable-speed battery fan. This PPV works with Milwaukee Red Lithium 28V batteries, making it the most compatible PPV interface on the market. This nimble fan weighs only 53 lbs. and is 24.25" tall x 23.75" wide x 12.25" deep, turning this fan into the industry's lightweight champ.

Frame Features

- 1 Compact, Roll-Cage Frame:** Features a tough yet lightweight aluminum frame to protect key components while providing a compact, lightweight design
- 2 Fold-Down Ergonomic Handle:** Folds into the frame for compact storage; features full-width handle for easy grip with heavy-duty gloves
- 3 Flat-Proof Rubber Tires:** Highly maneuverable, and all without lifting the fan; easy to deploy by the smallest firefighters.
- 4 180-Degree Tilt:** Provides the largest tilt range among battery fans, allowing airflow to be directed virtually anywhere

Fan Features

- 5 Milwaukee REDLITHIUM 28V batteries:** Batteries provide up to 52 minutes of run time, depending on battery selection; optional 120-240V AC operation is available upon request
- 6 Polymer Blade:** Minimizes weight; Super Vac's single-piece cast aluminum blade is available by request
- 7 Precision-Spun Steel Shroud with StreamShaper Guard:** Shroud provides durability with max airflow, while the StreamShaper guard allows for flexible setback; Air Cone Guard available by request

16" Blades - H x W x D: 24.25" x 23.75" x 12.25" - 615mm x 605mm x 315mm

Model	Weight With Batteries and Shore Power	Motor	Setback For Output Rating	Angle For Output Rating	AMCA 240-22 Certified Output
V16-BW-SP-WH	53 lbs 24 kg	Totally Enclosed Variable-Speed DC	15 ft 4.6 m	10°	8,084 cfm* 13,735 cmh*

*See back for disclaimer.



Battery Options

Compatible Battery	Run Time
Milwaukee M28 REDLITHIUM™ XC3.0 (2)	31 minutes (With built-in battery gauge)
Milwaukee M28 REDLITHIUM™ XC5.0 (2)	52 minutes (With built-in battery gauge)

120-240V AC operation is standard (with optional delete).

**5-YEAR
WARRANTY**

3-YEAR WARRANTY
ON MOTOR/BATTERIES



POSITIVE PRESSURE VENTILATOR

A Super Vac, part number V16-BW-SP-WH, 16" variable-speed battery fan shall be supplied. The unit shall be designed with a lightweight roll-cage frame with strategic placement of bracing members to enable easy carrying of the fan.

The entire frame of the unit shall be constructed of aluminum that shall surround the shroud and a six-blade 16" airfoil propeller in a roll-cage design, which shall enhance lifting and user safety. The blade shall be constructed of polymer and driven by an battery-powered motor with a direct drive connection. Any ventilators utilizing belts, pulley, gears or additional shafts shall not be acceptable.

The unit shall be compatible with dual Milwaukee Red Lithium 28V battery system (dual 3Ah or 5Ah batteries) that is commercially available for low cost and ease of replacement. A dual 5Ah battery system shall enable the fan to operate for up to 52 minutes on a single charge delivering a maximum amount of airflow; the 3.0Ah battery system shall operate for up to 31 minutes. Fans using proprietary battery systems shall not be acceptable due to higher cost and limited supply.

The shroud and the safety grill shall be designed to provide maximum air velocity. The positive pressure ventilator shall have 180-degree tilt capability. The front and rear safety guards shall be designed to OSHA and U.L. Standards to prevent accidental contact with the blade.

The fan shall include shore power, allowing continuous operation off any 120-240V AC supply.

The air movement shall meet 8,084 cubic feet per minute. Results must be based on data documented during comparable AMCA 240-22 testing procedures.

Options:

Also available is a forward facing LED operated with a glove compatible push button. The LED light illuminates the scene and improves visibility of possible tripping hazards at the doorway.

The variable-speed battery fan shall be designed with the following:

Motor:	Totally Enclosed Variable-Speed DC
Power:	1 HP
Speed:	2,089 rpm
Airflow*:	8,084 cfm (13,735 cmh)
Dimensions:	24.25" x 23.75" x 12.25" (615mm x 605mm x 315mm)
Weight:	53 lbs. (24 kg) (Weight with batteries and shore power)

The PPV shall have a minimum five (5) year warranty. The battery and charger are warranted by Milwaukee for three (3) years. See www.milwaukeetool.com for details. Motor shall be warranted for a minimum of three (3) years.

*The listed ratings are based on tests and procedures in accordance with AMCA Standard 240-22. All other outputs in this chart are based on results from comparable AMCA 240-22 testing procedures. The AMCA 240 Standard was revised in 2022 to specifically test battery-powered PPV fans and was created in collaboration with industry experts, select firefighters and PPV manufacturers. The new test reflects improved variables, including a smaller doorway (to match international standards), constant power supply (since battery power drops over time) and documentation of battery runtimes (to assure accuracy). These variables deliver more accurate, yet lower airflows compared to identical fans tested to the old AMCA 240-16 standard.

