

718WT Positive Pressure Ventilators < Water Turbine Motor

A 18", water turbine PPV set on the classic 7-Series frame. A perfect combination of size and power for departments looking for an every day PPV fan that is not dependent on electricity and can be used in hazardous locations.

Features

- < 7 Point Cast Aluminum Airfoil Blade < holds up better than plastic in high heat
- < Precision Spun Steel Shroud < durability with maximum airflow
- < Full Roll Cage Steel Frame < protects key components
- < Solid Cushion Tires < heavy duty rubber, never flat, rolls up stairs and curbs
- < 4 Position Tilt Frame < tilt shroud to 4 angles (18°, 10°, 0°, -10°)
- < Step Brake System < foot pedal locks fan in place
- < Air Cone Guard < classic design, StreamShaper Guard optional
- < Fold Down Handle < folds down within frame for easy, compact storage
- < Compatible With Super Vac Accessories
 - < Spiral Duct
 - < Mountain Mister
 - < Foam Generator
 - < LED Holder
- < 5 Year Warranty

Specs

Motor < 5.5 Hp Water Turbine

Power Requirement < 100-250 psi

HxWxD < 21.75" x 22.5" x 18.75" < 552mm x 572mm x 476mm

Blade Diameter < 18" < 457mm

Weight < 76 lbs < 34.5 kg

Output < 16,830 cfm < 28,595 cmh





POSITIVE PRESSURE VENTILATOR

A Super Vac, part number #718WT, 18" water powered pressure ventilator shall be supplied. The unit shall be cart style designed with rear mounted wheels, a full height frame, and a tilt-up, full width handle for easy positioning and rapid deployment. All components of the positive pressure ventilator shall 100% manufactured and assembled in the United States.

The pneumatic wheels shall be designed with a "one step" braking system utilizing a single foot operated brake pedal to assure positive engagement to prevent the unit from rolling during operation. The unit shall remain stationary while running at full speed.

The entire frame of the unit shall be constructed of steel that shall surround the shroud and the seven-blade 18" airfoil propeller in a roll cage design that shall enhance lifting and user safety. The blade shall be constructed of precision cast of aluminum alloy #A356. The blade shall be driven by the gas engine that shall have a direct drive connection. Any ventilators utilizing belts, pulley, gears, or additional shafts shall not be acceptable. Any ventilators using plastic or nylon blades shall not be acceptable due to the high radiant heat found on fire scenes.

The positive pressure ventilator shall be powered by a 5.5 horsepower water motor using approximately 100 GPM while operating at 150 PSI. The unit shall have a 1.5 inch NST inlet and outlet.

The shroud and the safety grill shall be designed as to provide maximum air velocity. The positive pressure ventilator shall have a tilt control with four positions including one position that can direct airflow downward and shall be equipped with a lever to set positions of the air flow to 18, 10, 0, and -10 degrees above and below horizontal level.

The front and rear safety guards shall be designed to OSHA and U.L. Standards to prevent accidental contact with the blade.

The positive pressure ventilator shall be designed with the following:

Motor Manufacturer:	POK Water Turbine
Horsepower:	5.5HP
Cubic feet per minute:	16,830 CFM
Dimensions:	21.75" high x 22.50" wide x 18.75" deep
Weight:	76 pounds

The positive pressure ventilator shall have a minimum five (5) year warranty. The engine shall be warranted by the engine manufacturer for a minimum of two (2) years.