

## P164B Electric Smoke Ejector

Powered by a Super Vac IonPac 2.0 battery, this 16" battery-powered smoke ejector can operate for 30 minutes to 2 hours on a full charge while maintaining the same output as other 16" electrical smoke ejectors. The battery also can be plugged into a 115V AC power source to run the fan and charge simultaneously. Super Vac smoke ejectors are designed to pull smoke from structures using negative pressure, or they can be flipped around for positive pressure tactics.

### Features

- 1 Patented 4-Tip Recurved Aluminum Blade:** Creates a tight spiral of air to eject smoke and fumes away from the building; aluminum holds up better than plastic in high heat
- 2 Precision-Balanced Blade:** Maximizes output
- 3 Heavy-Duty Rubber Feet:** Adds friction to keep fan in place
- 4 4 Carry Handles:** Makes transportation easy with one or two people
- 5 Front and Rear Guards:** Prevents accidental contact with key components

### Compatible with these Super Vac Accessories:

Spiral Duct, Mountain Mister, Tilt Frame, Foam Generator and Door Bar/Hanger



**5-YEAR  
WARRANTY**

**16" Blades - H x W x D: 19.25" x 18.75" x 13" - 489mm x 477mm x 330mm**

Model	Weight	Motor	Run Time	Output
P164B	35 lbs 16 kg	Leeson, variable speed, 1 Hp, 24V Lithium Ion Battery Battery adds 31 lbs (14 kg)	60 min - 1,000 cycles; can be plugged into 115V AC	<b>Shroud:</b> 3,200 cfm - 5,435 cmh <b>Venturi:</b> 5,200 cfm - 8,835 cmh

## ELECTRIC SMOKE EJECTOR

A Super Vac, part number #P164B, 16" battery powered smoke ejector shall be supplied. The unit shall feature square construction for strength and stability. The unit shall be designed with four (4) carrying handles on each corner for easy positioning and rapid deployment. All components of the smoke ejector shall be 100% manufactured and assembled in the United States.

The smoke ejector shall be powered by a battery-powered motor with a supplied 24V lithium ion battery pack. The battery shall be able to be plugged into any 115- or 230-volt system.

The entire frame of the unit shall be constructed of steel and shall surround the four-blade 16" recurve tip blade to enhance lifting and user safety. The blade shall be constructed of precision-cast aluminum alloy #713. The blade shall be precision balanced and attached to the engine shaft for a direct drive connection. Any smoke ejectors utilizing belts, pulley, gears or additional shafts shall not be acceptable.

The unit shall be designed to attach a ventilation air duct to either the inlet or outlet side of the fan. The unit shall be designed to be used in conjunction with either a spiral or "L" air ducting and its Super Vac adapters.

The front and rear safety guards shall be designed to OSHA and U.L. Standards to prevent accidental contact with the blade. The unit shall be tested to AMCA 210 for air movement and the air movement shall exceed 3,200 cubic feet per minute.

The smoke ejector shall be designed with the following:

Motor:	Leeson Variable-Speed Motor with 24V Lithium Ion Battery
Horsepower:	1HP
Power:	115/230V, 50/60Hz
Output:	3,200 cfm
Dimensions:	19.25" high x 18.75" wide x 13" deep
Weight:	35 lbs. (Battery adds 31 lbs.)

The smoke motor shall have a minimum five (5) year warranty. The motor shall be warranted by the motor manufacturer for a minimum of two (2) years.

