

V18-BL PPV Electric Motor with Milwaukee Red Lithium 18V batteries

Never in firefighter history has one fan worked with your department's other battery-operated tools. Until now. The all-new Super Vac 18" variable-speed battery fan, equipped with Milwaukee Red Lithium 18V batteries, is the most swappable PPV interface on the market. Finally, the industry can turn to a fan with a trusted battery name that pairs with Super Vac's dependable history.

Frame Features

- 1 **Compact, Roll-Cage Frame:** Features a tough yet lightweight aluminum frame to protect key components while providing a compact, lightweight design
- 2 **Fold-Down Ergonomic Handle:** Folds into the frame for compact storage; features full-width handle for easy grip with heavy-duty gloves
- 3 **Flat-Proof Rubber Tires:** Highly maneuverable, and all without lifting the fan; easy to deploy by the smallest firefighters.
- 4 **180-Degree Tilt:** Provides the largest tilt range among battery fans, allowing airflow to be directed virtually anywhere

Fan Features

- 5 **Milwaukee Red Lithium 18V batteries:** Batteries provide up to 45 minutes of max airflow, depending on battery selection; optional 120-240V AC operation is available upon request
- 6 **Polymer Blade:** Minimizes weight; Super Vac's single-piece cast aluminum blade is available by request
- 7 **Precision-Spun Steel Shroud with StreamShaper Guard:** Shroud provides durability with max airflow, while the StreamShaper guard allows for flexible setback; Air Cone Guard available by request

18" Blades - H x W x D: 25.75" x 25.75" x 11.75" - 654mm x 654mm x 298mm

Model	Weight With Batteries	Motor	Setback For Output Rating	Angle For Output Rating	AMCA Certified Output
V18-BL	46 lbs 21 kg	Variable-Speed DC with Optional 120-240V AC	15 ft 4.6m	10°	10,840 cfm 18,417 cmh



Battery Options

Battery Type	Run Time At Max Airflow
 Standard Battery Milwaukee Red Lithium 18V 9.0Ah (2)	35 minutes (With built-in battery gauge)
 Optional Battery Milwaukee Red Lithium 18V 12.0Ah (2)	45 minutes (With built-in battery gauge)

*Milwaukee batteries NOT compatible with the Genesis or TNT Rescues Tools that use an older 28V platform.

POSITIVE PRESSURE VENTILATOR

A Super Vac, part number V18-BL, 18" battery operated positive pressure ventilator shall be supplied. The unit shall be designed with a lightweight roll-cage frame and include flat-proof rubber tires and an ergonomic handle that folds into the frame for easy positioning, rapid deployment and compact storage.

The entire frame of the unit shall be constructed of aluminum that shall surround the shroud and a six-blade 18" airfoil propeller in a roll-cage design, which shall enhance lifting and user safety. The blade shall be constructed of polymer and driven by an battery-powered motor with a direct drive connection. Any ventilators utilizing belts, pulley, gears or additional shafts shall not be acceptable. The unit shall be supplied with a dual Milwaukee Red Lithium 18V battery system that is commercially available for low cost and ease of replacement. Blowers using proprietary battery systems shall not be acceptable due to higher cost and limited supply. A dual 12Ah battery system shall enable the ventilator to operate for up to 45 minutes on a single charge delivering a maximum amount of airflow; the 9Ah battery system shall operate for up to 35 minutes.

The shroud and the safety grill shall be designed as to provide maximum air velocity. The positive pressure ventilator shall have 180-degree tilt capability.

The front and rear safety guards shall be designed to OSHA and U.L. Standards to prevent accidental contact with the blade. The unit must be licensed by AMCA for air movement and listed under PPV at amca.org. The air movement shall meet 10,840 cubic feet per hour.

The positive pressure ventilator shall be designed with the following:

Motor:	Totally Enclosed Variable-Speed DC
Power:	1Hp
Speed:	2,032 rpm
Output:	10,840 cfm (18,714 cmh) per AMCA Standard 240
Dimensions:	25.75" x 25.75" x 11.75" (654mm x 654mm x 298 mm)
Weight:	46 lbs. (21 kg) (Weight without shore power.)

The PPV shall have a minimum five (5) year warranty. The battery and charger are warranted by Milwaukee for three (3) years. See www.milwaukeeetool.com for details.

