

## V18-BD Variable-Speed Battery Fan

Never in firefighter history has one battery fan worked together with your department's other DeWalt battery-operated tools. Introducing the all-new Super Vac 18" variable-speed battery fan, equipped with dual DeWalt FLEXVOLT® batteries, making this rugged yet compact fan the most swappable PPV interface on the market. Finally, the industry can turn to a fan with a trusted battery name that pairs with 180+ products, including our fan and Super Vac's dependable history.

### Frame Features

- 1 Compact, Roll-Cage Frame:** Features a tough yet lightweight aluminum frame to protect key components while providing a compact, lightweight design
- 2 Fold-Down Ergonomic Handle:** Folds into the frame for compact storage; features full-width handle for easy grip with heavy-duty gloves
- 3 Flat-Proof Rubber Tires:** Highly maneuverable, and all without lifting the fan; easy to deploy by the smallest firefighters.
- 4 180-Degree Tilt:** Provides the largest tilt range among battery fans, allowing airflow to be directed virtually anywhere

### Fan Features

- 5 DeWalt FlexVolt Lithium Ion Batteries:** Batteries provide up to 45 minutes of max airflow, depending on battery selection; optional 120-240V AC operation is available upon request
- 6 Polymer Blade:** Minimizes weight; Super Vac's single-piece cast aluminum blade is available by request
- 7 Precision-Spun Steel Shroud with StreamShaper Guard:** Shroud provides durability with max airflow, while the StreamShaper guard allows for flexible setback; Air Cone Guard available by request

**18" Blades** - H x W x D: 25.75" x 25.75" x 11.75" - 654mm x 654mm x 298mm

Model	Weight With Batteries	Motor	Setback For Output Rating	Angle For Output Rating	AMCA Certified Output
V18-BD	46 lbs 21 kg	Totally Enclosed Variable-Speed DC	15 ft 4.6m	10°	10,840 cfm 18,417 cmh



### Battery Options



#### Standard Battery

DeWalt FLEXVOLT 9.0Ah (2)  
(Compatible with all DeWalt  
20/60/120V MAX Tools)

#### Run Time At Max Airflow

35 minutes  
(With built-in  
battery gauge)



#### Optional Battery

DeWalt FLEXVOLT 12.0Ah (2)  
(Compatible with all DeWalt  
20/60/120V MAX Tools)

#### Run Time At Max Airflow

45 minutes  
(With built-in  
battery gauge)

\*Up to 45 minutes run time, depending on battery selection. 120V MAX is based on using 2 DEWALT 60V MAX\*lithium-ion batteries combined. Optional 120-240V AC operation is available upon request.



## POSITIVE PRESSURE VENTILATOR

A Super Vac, part number V18-BD, 18" battery operated positive pressure ventilator shall be supplied. The unit shall be designed with a lightweight roll-cage frame and include flat-proof rubber tires and an ergonomic handle that folds into the frame for easy positioning, rapid deployment and compact storage.

The entire frame of the unit shall be constructed of aluminum that shall surround the shroud and a six-blade 18" airfoil propeller in a roll-cage design, which shall enhance lifting and user safety. The blade shall be constructed of polymer and driven by an battery-powered motor with a direct drive connection. Any ventilators utilizing belts, pulley, gears or additional shafts shall not be acceptable.

The unit shall be supplied with a dual DeWalt FLEXVOLT® lithium-ion battery system that is commercially available for low cost and ease of replacement. Blowers using proprietary battery systems shall not be acceptable due to higher cost and limited supply. A dual 12Ah battery system shall enable the ventilator to operate for up to 45 minutes on a single charge delivering a maximum amount of airflow; the 9Ah battery system shall operate for up to 35 minutes.

The shroud and the safety grill shall be designed as to provide maximum air velocity. The positive pressure ventilator shall have 180-degree tilt capability.

The front and rear safety guards shall be designed to OSHA and U.L. Standards to prevent accidental contact with the blade. The unit must be licensed by AMCA for air movement and listed under PPV at [amca.org](http://amca.org). The air movement shall meet 10,840 cubic feet per minute.

The positive pressure ventilator shall be designed with the following:

Motor:	Totally Enclosed Variable-Speed DC
Power:	1Hp
Speed:	2,032 rpm
AMCA Certified Airflow:	10,840 cfm (18,714 cmh)
Dimensions:	5.75" x 25.75" x 11.75" (654mm x 654mm x 298 mm)
Weight:	46 lbs. (21 kg) (Weight without shore power)

The PPV shall have a minimum five (5) year warranty. The battery and charger are warranted by DeWalt for three (3) years. See [www.dewalt.com](http://www.dewalt.com) for details.

