

## V18-BL-SP Variable-Speed Battery Fan

Never in firefighter history has one fan worked with your department's other battery-operated tools. Until now. This PPV works with Milwaukee REDLITHIUM 18V batteries, making it the most compatible PPV interface on the market. Finally, the industry can turn to a fan with a trusted battery name that pairs with Super Vac's dependable history.

### Frame Features

- 1 Compact, Roll-Cage Frame:** Features a tough yet lightweight aluminum frame to protect key components while providing a compact, lightweight design
- 2 Fold-Down Ergonomic Handle:** Folds into the frame for compact storage; features full-width handle for easy grip with heavy-duty gloves
- 3 Flat-Proof Rubber Tires:** Highly maneuverable, and all without lifting the fan; easy to deploy by the smallest firefighters.
- 4 180-Degree Tilt:** Provides the largest tilt range among battery fans, allowing airflow to be directed virtually anywhere

### Fan Features



- 5 Milwaukee REDLITHIUM 18V batteries:** Batteries provide up to 40 minutes of run time, depending on battery selection; 120-240V AC operation is standard (with optional delete).
- 6 Polymer Blade:** Minimizes weight; Super Vac's single-piece cast aluminum blade is available by request
- 7 Precision-Spun Steel Shroud with StreamShaper Guard:** Shroud provides durability with max airflow, while the StreamShaper guard allows for flexible setback; Air Cone Guard available by request

**18" Blades** - H x W x D: 25.50" x 26" x 12.25" - 650 mm x 660 mm x 315 mm

Model	Weight With Batteries and Shore Power	Motor	Setback For Output Rating	Angle For Output Rating	Output
V18-BL-SP	58 lbs 26 kg	Variable-Speed DC	15 ft 4.6m	12°	9,618 cfm 16,341 cmh



### Battery Options

Compatible Battery	Run Time
 Milwaukee REDLITHIUM™ HIGH OUTPUT™ XC8.0 (2)	30 minutes (With built-in battery gauge)
 Milwaukee REDLITHIUM™ HIGH OUTPUT™ HD12.0 (2)	40 minutes (With built-in battery gauge)

\*Up to 40 minutes run time, depending on battery selection.  
\*Milwaukee batteries NOT compatible with the Genesis or TNT Rescues Tools that use a 28V platform. 120-240V AC operation is standard (with optional delete).



## POSITIVE PRESSURE VENTILATOR

A Super Vac, part number V18-BL-SP, 18" battery operated positive pressure ventilator shall be supplied. The unit shall be designed with a lightweight roll-cage frame and include flat-proof rubber tires and an ergonomic handle that folds into the frame for easy positioning, rapid deployment and compact storage.

The entire frame of the unit shall be constructed of aluminum that shall surround the shroud and a six-blade 18" airfoil propeller in a roll-cage design, which shall enhance lifting and user safety. The blade shall be constructed of polymer and driven by a battery-powered motor with a direct drive connection. Any ventilators utilizing belts, pulley, gears or additional shafts shall not be acceptable.

The unit shall be compatible with a Milwaukee REDLITHIUM 18V battery system (XC8.0 or HD12.0 batteries) that is commercially available for low cost and ease of replacement. Blowers using proprietary battery systems shall not be acceptable due to higher cost and limited supply. A dual 12Ah battery system shall enable the ventilator to operate for up to 40 minutes on a single charge; the 8Ah battery system shall operate for up to 30 minutes.

The shroud and the safety grill shall be designed as to provide maximum air velocity. The positive pressure ventilator shall have 180-degree tilt capability.

The front and rear safety guards shall be designed to OSHA and U.L. Standards to prevent accidental contact with the blade. The unit must be licensed by AMCA for air movement and listed under PPV at [amca.org](http://amca.org). The air movement shall meet 9,618 cubic feet per minute.

The fan shall include shore power, allowing continuous operation off any 120-240V AC supply.

The positive pressure ventilator shall be designed with the following:

Motor	Totally Enclosed Variable-Speed DC
Power:	1 HP
Speed:	2,032 rpm
Output:	9,618 cfm (16,341 cmh)
Dimensions:	25.50" x 26" x 12.25" (650 mm x 660 mm x 315 mm)
Weight:	58 lbs. (26 kg) (Weight with batteries and shore power.)

The PPV shall have a minimum five (5) year warranty. The battery and charger are warranted by Milwaukee for three (3) years. See [www.milwaukeetool.com](http://www.milwaukeetool.com) for details. Motor shall be warranted for a minimum of three (3) years.

