

P8XE-220V Electric Nano Confined Space Fan

Meet the market's smallest, most powerful confined space fan, designed for confined space ventilation challenges with unknown gases and potentially dangerous environments. This 8" fan delivers the highest airflow in its class and can be used to supply clean air to a space or can be use to exhaust fumes from the area. The P8XE is powered by a motor rated for Class 1 Group D environments.

Features

- ❶ **Versatile:** Can be used for positive or negative pressure operations; the duct can be attached to either end
- ❷ **2 Carry Handles:** Provides easy transport



**5-YEAR
WARRANTY**

8" Blades - H x W x D: 11.5" x 10.75" x 16" - 295mm x 275mm x 406mm

Model	Weight	Motor	Output	NANO PACS
P8XE-220V	22 lbs 10 kg	1/3 HP, hazardous location rated for Class 1 Group D, 50Hz, 220V AC	1,054 cfm 1,790 cmh	Available kit with 15' or 25' conductive duct



ELECTRIC CONFINED SPACE FAN

A Super Vac Nano P8XE, 8" electric confined space fan shall be supplied. The unit shall feature a square construction design for strength and stability. The unit shall be designed with two (2) carrying handles on each corner for easy positioning and rapid deployment. All components of the smoke ejector shall be 100% manufactured and assembled in the United States.

The confined space fan shall be powered by a 1/3 Horsepower electric motor that is listed by Underwriters Laboratory (UL) for Hazardous Locations up to and including Class 1, Group D.

The entire housing of the unit shall be constructed of weather- and corrosion-resistant, high-impact polyethylene conductive plastic with a full aluminum liner. The blade shall be constructed of Electro Anti-Static Glass Reinforced Polyamide (PAGAS – Nylon) and rated from -40° F to +248°F. The blade shall be precision balanced and attached to the engine shaft for a direct-drive connection. Any confined space fan utilizing belts, pulley, gears or additional shafts shall not be acceptable.

The front and rear safety guards shall be designed to OSHA and U.L. Standards to prevent accidental contact with the blade.

The unit shall be designed to accept a ventilation air duct to either the inlet or outlet side of the fan. The unit shall be designed to be used in conjunction with either a spiral or "L" air without any additional adapters required.

The confined space fan shall be designed with the following:

Motor Manufacturer:	Bluffton Electric Motor
Horsepower:	1/3 HP
Voltage:	50Hz, 220V AC
Output:	1,054 CFM

Dimensions: 11.5" High x 10.75" Wide x 16" Deep
(295mm x 275mm x 406mm)

Weight: 22 lbs.

The confined space fan shall have a minimum five (5) year warranty. The motor shall be warranted by the motor manufacturer for a minimum of two (2) years.

OPTIONAL DUCT

A Super Vac, conductive duct for Nano shall be supplied. The duct shall be constructed from a single-ply of conductive neoprene-coated polyester material and shall be supported by a continuous spring steel wire helix. The Nano conductive duct is produced with a specially formulated conductive compound, which in turn provides a superb way to dissipate static build-up when the duct is properly grounded. Conductive material shall be rated to 100,000 ohms or less per square inch.

The duct shall come with a built-in carry bag that duct contracts into for easy transportation.

The duct shall include heavy-duty vinyl wearstrip with self-adhering neoprene backing, approximately 25-27 oz. square yard. Abrasion resistance of 18,000 cycles from H-22 wheel with 1,000 gram load (FSTM 191 Method 5306).

A Class 1 hard-drawn spring steel wire helix that conforms to ASTM 227 specifications shall be in place to support the duct.

The duct shall have produced to UL94-V-0 flame retardancy specifications / MINS 540-106-1 (Mare Island Naval Shipyard) / California T-19 / NFPA 701 - Large Scale.

The product shall be grounded on each end with a solid means of connection. Grounding this product on one end only will still provide a safe positive means of discharging static build-up. Grounding straps shall be provided at the wire terminations ends.