

P200S-AL Electric Smoke Ejector

This 20" electric, single-speed Super Vac Smoke Ejector packs high-powered air movement — all while running on a 15-amp household circuit — perfect for departments with larger residential buildings in their jurisdictions. This fan pulls smoke from structures using negative pressure but can be flipped around for positive pressure tactics. Smoke ejectors are most effective when working with natural airflow and not against Mother Nature.

Features

- 1 **Aluminum Frame Design:** Lightweight, compared to traditional steel smoke ejectors
- 2 **Patented 4-Tip Recurved Aluminum Blade:** Holds up better than plastic in high heat
- 3 **Precision-Balanced Blade:** Maximizes output
- 4 **Heavy-Duty Rubber Feet:** Heavy duty rubber adds friction to keep fan in place
- 5 **4 Carry Handles:** Makes transportation easy with one or two people
- 6 **Front and Rear Guards:** Prevents accidental contact with key components



**5-YEAR
WARRANTY**

Compatible with Accessories:

Spiral Duct, Tilt Frame, Foam Generator, Vinyl Cover, Door Bar/Hanger, Running Board Mount

20" Blades - H x W x D: 25.5" x 24.75" x 16.25" - 650 mm x 630 mm x 415 mm

Model	Weight	Motor	RPM	Start	Run	Output
P200S-AL	70 lbs 32 kg	WEG, single speed, TEAO, 1 HP, 50/60Hz, 115/230V AC; Aluminum Frame Design (vs. Steel)	1,725	4,000 w 15-amp circuit	1,500 w	9,800 cfm 16,650 cmh

ELECTRIC SMOKE EJECTOR

A Super Vac, part number #P200S-AL, 20" electric smoke ejector shall be supplied. The unit shall feature square construction for strength and stability. The unit shall be designed with four (4) carrying handles on each corner for easy positioning and rapid deployment. All components of the smoke ejector shall be 100% manufactured and assembled in the United States.

The blade shall be driven by a 1 Horsepower Bluffton electric motor that shall be operational with any 115- or 230-volt system. The unit shall be designed with a totally enclosed air over motor casing to ensure the motor protection.

The entire frame of the unit shall be constructed of aluminum and shall surround the four-blade 20" recurve tip blade to enhance lifting and user safety. The blade shall be constructed of precision cast aluminum alloy #319. The blade shall be precision balanced and attached to the engine shaft for a direct drive connection. Any smoke ejectors utilizing belts, pulley, gears or additional shafts shall not be acceptable.

The unit shall be designed to attach a ventilation air duct to either the inlet or outlet side of the fan. The unit shall be designed to be used in conjunction with either a spiral or "L" air ducting and its Super Vac adapters.

The front and rear safety guards shall be designed to OSHA and U.L. Standards to prevent accidental contact with the blade. The unit shall be tested to AMCA 210 for air movement and the air movement shall exceed 9,800 cubic feet per minute.

The smoke ejector shall be designed with the following:

Motor:	WEG Totally Enclosed Air Over (TEAO) Electric
Horsepower:	1 HP
Power Supply:	115/230V AC, 50/60Hz
Speed:	1,725 rpm
Output:	9,800 cfm
Dimensions:	25.5" high x 24.75" wide x 16.25" deep (650 mm x 630 mm x 415 mm)
Weight:	70 lbs.

The smoke ejector shall have a minimum five (5) year warranty. The motor shall be warranted by the motor manufacturer for a minimum of two (2) years.

